

Type B80 Microphone

Shockproof, Waterproof, Vibration Proof

VITAVOX

Vitavox Type B80 Microphone is fully shockproof, waterproof and vibration proof. This unit is most suitable for installation in exposed conditions where its robust construction can appropriately withstand heavy duty for long periods. Two versions are available; ATEX approved and Not ATEX approved.

Part no.	NSN no.	ATEX approved
VT07491	5965-99-425-3286	Certified ATEX approved
VT07240	No NSN number	Not ATEX approved

- Conforms to shock, vibration and waterproofing requirements of DEF-133, Class N1 and SES-5
- Approved at intrinsically safe ATEX EN13980 94/9/EC for use in flammable atmospheres (Groups 2a, 2c, 2d, 2e) when mounted in permanent position and installed in accordance with Drawing No.1563, SIRA Cert. M0953
- Non ATEX approved version also available
- Microphone and switch assembly housed in aluminum Type LM6M watertight case
- Withstand heavy duty for long periods without attention
- Inside case panel is screw terminal for connections to switched moving coil microphone inset
- Slotted shaft protrudes front panel which changes the switch mechanism from spring return to "OFF", to click lock in "ON"



TYPE B80 MICROPHONE

Optimum load impedance:	25Ω
Output level at 1 kHz:	65 dB below 1V/Pa
Frequency response:	60 - 8000 Hz
Weight:	0.68 kg
Cable:	2m long, supplied only with intrinsically safe version

See more of the Vitavox land and maritime range at:

www.vitavox-sound.com

T: +44 (0)208 732 1300

F: +44 (0)208 732 1301

E: sales@vitavox-sound.com

Vitavox™ (a division of Secomak Ltd.)

330 Centennial Park, Elstree, Hertfordshire, WD6 3TJ, UK. Telephone: +44 (0) 20 8732 1300
Fax: +44 (0) 20 8732 1301 Email: sales@vitavox-sound.com Web: www.vitavox-sound.com